



R2 Beam Wash

LEDMOV422

The R2 Beam Wash driven by 19 x 40W RGBWW LED Chips has an amazing, bright output. The full pixel control allows for endless creativity and great eye candy effects. With smooth 16bit dimming this fixture is also a great option for Theatrical applications. Dual RJ45 ports provides different connectivity options allowing for future proofing. The native warm white LED's provide a spectacular colour palette with amazing CCT's only achievable with this LED combination. High intensity beam mode and super wide wash make this a truly flexible beam/wash fixture





 SYDNEY
 MELBOURNE

 +61297481122
 +61396817511

BRISBANE 11 +61 7 3267 3177 PERTH +61892488119





Specifications

Optical System

Lamp Source	19 x 40W RGBWW
Linear Zoom	4° to 60°
ССТ	2700K to 8000K

Electrical Specifications

Voltage	100 – 240VAC 50/60Hz
Max Power	858W
Power Connection	PowerCon In/Out
Signal Connection	5pin DMX In/Out, 2x RJ45

Work Environment

IP Rating

IP20

Control System

Dimmer	0 to 100% 16-bit
Pan/Tilt	540°/270° 16 bit
Cooling	Variable Speed Fan
Control	DMX512, RDM, Artnet
Personality	14ch/43ch/86ch
Appearance	
Size	419 x 277 x 492mm

Weight	19kg
Casing	Plastic and Aluminium
Colour	Black

Photometrics

4° RGBW Beam					
Beam	Angle: 4°				7
o	ice (lux) on distance (m)	0	$\left(\right)$		
riojectie	1m	3m	5m	7m	10m
R		3m 22166	5m 7980	7m 4071	10m 1995
	1m				
R	1m 199500	22166	7980	4071	1995
R G	1m 199500 460000	22166 51111	7980 18400	4071 9387	1995 4600

32° RGBW Beam

Dearn	Angle: 32°			0	$- \wedge$
o Luminan Projectio	ice (lux) on distance (m)	0	$\left(\right)$	$\left(\right)$	
	60	3m	5m	7m	10m
	1m	200			
R	1m 5680	631	227	116	56.8
G				116 289	
G	5680	631	227		56.8 141.6 24
R G B W	5680 14160	631 1573	227 566.4	289	141.6



 SYDNEY
 MELBOURNE
 BRISBANE
 PERTH
 AUCKLAND

 +61297481122
 +61396817511
 +61732673177
 +61892488119
 +6498693293

