

# Eclipse Profile Zoom RGBAL

LEDPRO050

The Eclipse Profile Zoom RGBAL is a compact and lightweight RGBAL profile that's designed to impress. With a high CRI and a large CCT range from 1800K to 10,000K this fixture has got you covered. Featuring an integrated structural design, seamlessly incorporating the shutter framing system and boasting a manual zoom range of 25-50° this is a versatile and compact all in one package. With CCS colour consistency control technology, it is easy to colour match with other compatible fixtures in the Silverstar range.



# Specifications

## Optical System

Lamp Source	150W RGBAL
Beam Angle	25° to 50°
CRI	93
CCT	1800K to 10,000K

## Electrical Specifications

Voltage	100 – 240VAC 50/60Hz
Max Power	170W
Power Connection	True1 In/Out
Signal Connection	5pin DMX In/Out

## Work Environment

Ambient Temperature	0°C to 45°C
IP Rating	IP20

## Control System

Dimmer	0 to 100% 16-bit
Cooling	Forced Convection
Control	DMX512, RDM
Display	On board control
Personality	Basic(3), SSP(7), HSIC(7), Tour(12), TR16(18)

## Appearance

Size	568 x 224 x 191mm
Weight	5.8kg
Casing	Flame retardant plastic
Colour	Black

## Optional Accessories

**LEDPRO051- Gobo Holder (M)**

## Photometrics

