



Colour Ranger 48

LEDWSH482

The Colour Ranger 48 is an IP66 rated architectural wash suitable for both outdoor and indoor deployment and installations. The Aluminium Die Cast construction makes the Colour Ranger extremely durable and allows the fixture to be passively cooled, providing reliable performance as well as low maintenance requirements. The LED array formed of 48 x 13.8W RGBW chips provides an impressive output and the ability for segment control of four horizontal sections.



Colour Ranger 48 Specifications

Optical System

Lamp Source	48 x 13.8W RGBW LED
Beam Angle	8°
CCT	2800K to 10,000K
CRI	≥90


Electrical Specifications

Voltage	100 - 240VAC 50/60Hz
Max Power	460W
Power Connection	IP molded in/out power connectors with 240V AC adaptor included
Signal Connection	IP molded in/out data connectors with XLR adapters included

Work Environment


Ambient Temperature	-20°C to 45°C
IP Rating	IP66


Photometrics



Projection Distance (m)	1m	3m	5m	7m	10m
Luminance (Lux)					
R G B W ALL	63900 126900 21150 136800 344700	7100 14100 2350 15200 38300	2560 5080 850 5470 13790	1300 2590 430 2790 7040	640 1270 2120 1370 3450

Dimensions





Control System

Dimmer	0 to 100% 8-bit
Cooling	Passive
Control	DMX512, RDM, W-DMX
Display	No display
Personality	4ch, 6ch, 10ch, 16ch
Tilt Angle (Manual)	+/-130°

Appearance

Size (LWH)	584 x 93 x 304mm
Weight	12.9kg
Casing	Aluminium Die Cast
Colour	Grey

Included Accessories

LEDWSH518 IP molded power adaptor

LEDWSH519 IP molded 5pin female adaptor

LEDWSH520 IP molded 5pin male adaptor

Optional Accessories

Diffusion (needs to be fitted):

LEDWSH495 40° diffusion filter

LEDWSH496 50° diffusion filter

LEDWSH496 60° diffusion filter

LEDWSH497 60x10° diffusion filter

LEDWSH498 60x30° diffusion filter

Molded Power Extensions:

LEDWSH511 1m power extension

LEDWSH512 2m power extension

LEDWSH515 5m power extension

LEDWSH516 10m power extension

LEDWSH517 20m power extension

Molded Data Extensions:

LEDWSH521 1m DMX extension

LEDWSH522 2m DMX extension

LEDWSH525 5m DMX extension

LEDWSH526 10m DMX extension

LEDWSH527 20m DMX extension