

Z8 STRIP FC

MUSBAT200

Z8STRIP is a new generation battery operated fixture that marks a new step in wireless lighting technology, being one of the brightest portable fixtures in the event industry.



FEATURES:

- 8x10W RGBW LEDs
- Pixel controlled
- W-DMX
- IP 65
- Up to 16 hours battery life in colour changing mode



Z8 STRIP

MUSBAT200

LIGHT SOURCE

Source:	8x10W RGBW LED
Lux:	4600lux @3m full
Source life expectancy:	>50.000 h

OPTICS

Beam Angle:	10°
Field Angle:	21°
Additional optics:	Magnetic holder for diffusion filters or gels

COLOUR SYSTEM

Colour mixing:	RGBW/FC
White presets:	3200~10000K
Colour wheel:	Virtual colour wheel with presets
Macros:	built-in white presets

DYNAMIC EFFECTS

Auto Mode:	built-in programs with execution speed adjustment
Static colour mode:	Selection of static colour
Manual colour mode:	Manual adjustment of colour

BODY

Body:	Sturdy polycarbonate body
Body colour:	Black

CONTROL

Protocols:	DMX512, RDM
DMX channels:	4 / 6 / 10 / 32 / 37 channel
Pixel control:	Pixel2pixel control
W-DMX:	Included, wireless solution receiver
Display:	black OLED touch display
W-DMX:	Included, wireless solution receiver
RDM:	RDM ready for fixture remote monitor and settings
Firmware upgrade:	Yes, via USB-DMX interface (UPBOX1) not inc
Master/Slave:	for synchronized operation of more units linked in a chain

ELECTRONICS

Dimmer:	Linear 0~100% electronic dimmer
Strobe / shutter:	1-25 Hz, electronic
Operating temperature:	-10° ~ +45°
Flicker:	Flicker-free operation

ELECTRICAL

Power supply:	100-240V – 50/60Hz
---------------	--------------------

BATTERY:

Battery:	11,1V lithium
Battery life in colour change mode up to:	10 hours
Estimated battery life in single mode :	15 hours
Estimated battery life in full-mode:	5 hours
Recharge connection:	Power cable
Recharge time:	5h/max
Battery status:	Shown on display

PHYSICAL

Cooling:	convection cooled
Suspension and fixing:	hanging bracket suitable for safe hanging and positioning
IP rating:	IP65 (front) - IP54 (bottom)- IP54 (bottom)
Dimensions (WxHxD):	800x153x216mm
Weight:	10 kg
Signal connection:	Seetronic XLR 5p IN/OUT connectors
Data connection:	W-DMX OEM TRX
Power connection:	Seetronic powerKon waterproof IN/OUT connectors

