

EclPar FC

150W RGB + Warm White HQ and flexible LED PAR

ORDER CODE: **ECLPARFC**



EclPar FC is a range of multipurpose LED fixtures with a single source, delivering silent operation, high quality of light and optical flexibility, designed to redefine the standard for theatrical, TV and corporate applications. **EclPar FC** features a 150W RGB + Warm White and delivers a superior white CTC with +/- tint control, red-shift (CRI > 95 and R9 > 98 @3.200 K) and colour mixing. The fixture includes an extensive range of accessories including barn doors, filter frame, egg crate and a multitude of interchangeable lenses. **EclPar FC** features a smooth 16-bit dimming as well as RDM control and adjustable PWM providing eye-candy.

MAIN FEATURES

- 150W RGB + Warm White delivering precise whites, +/-green correction (CRI > 95 and R9 > 98 @3.200 K) and colour mixing
- Flex lens system: 24° on-board - 73° included - 40° optional
- Silent operation and adjustable PWM

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 150W RGB + Warm White
- CCT: 2.800 K - 6.500K
- Luminous flux: (24°) 5'983 lm - (73°) 5'774lm @full
- Lux: (24°) 1'040 lx - (73°) 166lx @5 m full
- CRI: 95 @3.200 K; 92 @5.600 K
- R9: 98 @3.200 K; 96 @5.600 K
- TLCI: 85 @5.600 K
- TM30 Rf: 92 @3.200 K; 90 @5.600 K
- TM30 Rg: 105 @3.200 K; 106 @5.600 K
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: (on board) 24° or (included) 73°
- Field angle: (on board) 28° or (included) 104°
- Lens diameter: 163mm
- Lens type: fresnel lens
- Additional optics: 24° lens on board - 73° lens included - 40° lens optional - egg crate optional - barndoors optional - gel frame holder included
- Other: 12° lens not available

COLOUR SYSTEM

- Colour mixing: RGB + Warm White
- CCT: CCT control, + / - green correction, tungsten emulation
- White presets: 2.800 K - 6.500K
- Colour wheel: virtual colour wheel with macros
- Macros: built-in white presets

DYNAMIC EFFECTS

- Static mode: selection of static colour
- Manual mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment
- Special features: linear crossfade channel from any white to any colour; virtual CTO on colours

BODY

- Hardware on-board: on board mechanics for rigging to the ceiling

ACCESSORIES & RELATED PRODUCTS

- 9513FCAL03 Ass. 3x2.5mm TH07 cable, 16A 3p 230V CEE plug, MENAC3FCA socket, L.3m
- 9533FCAL03 Ass. 3x2.5mm TH07 cable, SHUKO plug, MENAC3FCA socket, L.3m
- 958025L03 3x2.5mm TH07 Cable, 20A 3p PwCon FCA, 20A 3p PwCon FCB, L. 3m
- C6002B Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
- ECLPARBD Barn door with directional flaps to adjust the light beam for ECLPAR series
- FCLECLPAR Flightcase for 6 pcs of ECLPAR
- RSR0630B Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black

- Body: sturdy die-cast aluminium body
- Body colour: black

CONTROL

- Protocols: DMX512, RDM
- DMX channels: (theatre) 1 / 2 / 4 / 5 / 6 / 10 / 15 / 17 ch - (tour) 4 / 6 / 10 / 15channel
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 30 Hz, electronic
- Operating temperature: -10° ~ +45°
- LED Control: flicker free operation
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 150W
- Output (at 230V): 14 units on a single power line
- Power factor: > 0.92

PHYSICAL

- IP rating: 20
- Cooling: active, silent operation
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: Amphenol XLR 3p + 5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- Dimensions (WxHxD): 316x404x317mm
- Weight: 5,7kg


CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM

- TOUR53413L03 Dmx cable HC5340. CANC3MXX XLR 3p->CANC3FXX XLR (f) 3p, L.3m
- TOUR53415L03 Dmx cable HC5340. CANC5MXX XLR 5p->CANC5FXX XLR (f) 5p, L.3m
- ECLPARLENS24 24° lens for ECLPAR projectors series
- ECLPARLENS40 40° lens for ECLPAR projectors series
- ECLPAREC Egg crate for ECLPAR projectors series
- ECLPARLENS65 73° lens for ECLPAR projectors series
- ECLPARTPG Gel filter frame for ECLPAR projectors
- ECLPARASF Kit di filtri asimmetrici per serie ECLPAR
- UPBOX1U Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT


PRESET FULL ON

Beam angle 50%: 24°




PRESET FULL ON

Beam angle 50%: 73°



TECHNICAL DRAWINGS



CERTIFICATIONS / APPROVALS



Visit our website for specifications and tech documentations